

Part Number: D1414D2201B



© Copyright Mann Tek AB

https://configurator.manntek.se/SWIVELS/SWIVEL_SINGLE/4/BR/THREAD/F_3_BSP_D/THREAD/F_3_BSP_D/VITON/B/Product11.html

Product Group

Swivel Joints

Standard type with single ball race allows free rotation between hose assembly and attached handling equipment such as filling nozzles.

Standard duty Swivel Joints are used e.g. in filling plants to avoid torsion of hose assemblies and improve the handling and coupling of nozzles if no integrated swivel is attached.

One capsulated ball bearing and PTFE bearing. Electrically conductive.

Designed to allow smooth rotation (slow rotary movement) of operating devices such as filling nozzles.

Not certified to bear side loads or high bending moments; for high bending movements, please use 'heavy duty' Swivel Joints.

Available sizes 3/4" (DN 19) up to 4" (DN 100). Special type 'Heavy Duty' with double ball race

allows free rotation between hose assembly and the fixed point of a plant / pipe system, e.g. tank truck or rail tanker connection.

Heavy duty Swivel Joints are designed especially for hose reels to load and unload products where high bending forces can occur - e.g. offshore hose reels ship-to-shore, oil platform loading rigs, hoses for road and rail tankers.

Two capsulated ball bearings. Electrically conductive.

Designed to allow smooth rotation (slow rotary movement) of hose assemblies which are attached to a fixed point of the pipework, e.g. rail tanker or tank truck connection.

Suitable to bear high bending moments. Do not use for strong side loads directly on the swivel.

Available sizes 2" (DN 50) up to 10" (DN 250).

Type of Coupling

Standard Duty

Standard type with single ball race

allows free rotation between hose assembly and attached handling equipment such as filling nozzles.

Standard duty Swivel Joints are used e.g. in filling plants to avoid torsion of hose assemblies and improve the handling and coupling of nozzles if no integrated swivel is attached.

One capsulated ball bearing and PTFE bearing. Electrically conductive.

Designed to allow smooth rotation (slow rotary movement) of operating devices such as filling nozzles.

Not certified to bear side loads or high bending moments; for high bending movements, please use 'heavy duty' Swivel Joints.

Body Material

Gun Metal

suitable e.g. for petroleum based products and various solvents

Maximum Working Pressure 16 bar

Test Pressure 24 bar

Minimum Burst Pressure 80 bar

Connection 1

Connection 1 - Detail

Threaded Connection

F 3" BSP

3" BSP female to EN ISO 228



Connection Detail

Connection 2

Connection 2 - Detail

Connection Detail

O-Rings

Technical Drawing

Other Threaded Connection

F 3" BSP

Technical Drawing

Viton® (or equivalent FPM/FKM) Standard

FKM/FPM (Fluorocarbon Rubber): FKM is known especially for its non-flammability, low gas permeability and excellent resistance to ozone, weathering and aging.

The operating temperatures of the Fluorocarbon Rubber range between -20° C and +200° C).

FKM is often used with mineral based oils and greases at high temperatures, aliphatic, aromatic and chlorinated hydrocarbons and oxidizing acids.

Flat Seal



PUR (Vulkollan®)

PDF Documents

📄 Homepage Swivel Joints (Swivel Joints)



Contact Data:

Mann Teknik AB
Strandvägen 16
SE-542 31 Mariestad / Sweden
Telefon: +46 501 39 32 00
Telefax: +46 501 39 32 09
Internet: <http://www.manntek.se>



MannTek

D1414B4401A-1
Swivel Joints
DN 80 (3")
F 3" BSP



MannTek

D1414B4401A-1
Swivel Joints
DN 80 (3")
F 3" BSP